



WLS 02 WLS 03



Available colours



Special colour additives

WLS are innovative color additives designed to create striking and unique visual effects. These products are specifically developed for waterborne mixing systems and can be used to reproduce challenging colors from brands like Mazda. The **WLS** line consists of two distinct mixes, offering a creative way to enhance individuality and achieve remarkable finishes. Designed to surprise and captivate, **WLS** brings advanced color technology to any paint system.

Available in 0,25-liter tins, it is a versatile solution for both custom and professional applications.

PACKAGING	
Volume	Collective packaging
0,25 l	6 pcs.



INTERESTING COLOURS



SATURATED AND VIVID COLOURS



INDIVIDUAL COLOURS



ADDED TO BASECOAT



RECOMMENDED SIZES FOR PAINT STRAINER
125 µm



PAINT EFFICIENCY according to the colour



COLOURS AVAILABLE:
- **WLS 02** Blue Metallic
- **WLS 03** Glass Effect



MODEL APPLICATION
step I coating according to formula e.g. **Nissan KBZ**
step II clearcoat application



MINIMUM SHELF LIFE
24 months in originally sealed packaging

PROCESS

PROCESS

PROCESS



SUBSTRATE PREPARATION
After preparing and abrading the primer surface, degrease with silicone remover **CP 015** and clean with **CP 011**, then apply the basecoat



MIXING RATIO
WLS is added to the waterborne system. For OEM codes, the amount of additive is determined by the recipe in the recipe software



SPRAY GUN SETTINGS
Nozzle size: **1.2-1.4 mm**;
Operating pressure: HVLP/RP **1.8-2.0 bar**



APPLICATION
Application is subject to the specific method and colour that the additive is used with



EVAPORATION TIME AFTER APPLICATION
10-15 min after application at **20°C** and **65%** relative humidity